

SIRIM QAS International Sdn. Bhd. (410334-X) No. 1, Persiaran Dato' Menteri, Section 2, P.O. Box 7035, 40700 Shah Alam, Selangor Darul Ehsan, Malaysia

Tel: 03-55445854/5856 Fax: 03-55445886 www.sirim-qas.com.my

## **FULL TYPE TEST REPORT**

REPORT NO: 2017CB2201

PAGE: 1 OF 2

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Managing Director, SIRIM QAS International Sdn. Bhd. Please refer overleaf of Page 1 for Conditions Relating to the Use of Test Report.

Applicant.

MAXIM MATERIALITY SDN. BHD.

No. 15, Jalan SBC 7, Taman Sri Batu Caves,

68100 Batu Caves, Selangor.

Manufacturer

\*

Product

**Envigal Welded Gabion** 

Reference Standard/

Company's Specification : -

Method of test

Tensile TestWelding Test

Description of sample :

One (1) sample of Envigal Welded Gabion was received for testing.

Brands: ENVIGAL™

Type: Welded Gabion size 1m (H) x 1m (W) x 3mm (wire diameter),

spacing 83mm x 83mm.

Product Description: Welded Gabion majorly used for retaining wall or

soil reinforcement.

Date and Location of

Sampling

29th November 2017

Job No./Ref. No.

J20171431891 /SQAS/CCST/T.REC/MSL/09

Description of test

results

The test results for the submitted test samples are described in Page 2

of this test report.

Issued date

1 5 JAN 2018

TION

Approved Signatory

(NORAZLAN ROSLANI)
Testing Executive

(YM RAJA NOR SIHA RAJA ABDUL HANAN)

Head

Civil & Construction Section Testing Services Department REPORT NO: 2017CB2201 PAGE: 2 OF 2

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Managing Director, SIRIM QAS International Sdn. Bhd. Please refer overleaf of Page 1 for Conditions Relating to the Use of Test Report.

SAMPLE REFERENCE : TENSILE TEST

CLAUSE	REQUIREMENT	RESULTS	REMARKS
MECHANICAL PROPERTIES			
Diameter, a (mm)	Company's Specifications	2.94	-
Yield Strength, R <sub>EH</sub> (N/mm²)		705	-
Tensile Strength, $R_m$ (N/mm <sup>2</sup> )		760	-
Elongation (%)		20.4	-

SAMPLE REFERENCE : WELDING TEST

CLAUSE	REQUIREMENT	RESULTS	AVERAGE
WELDING STRENGTH			
	Company's Specifications	2.73	2.56
Strength of weld, (kN)		2.72	
		2.22	

(The remainder of this page is intentionally left blank)

1 5 JAN 2018

